



DEPARTMENT OF EXTENSION EDUCATION
SKN COLLEGE OF AGRICULTURE,
SRI KARAN NARENDRA AGRICULTURE UNIVERSITY,
JOBNER – 303329 Distt. Jaipur (Raj.)

No: Ext.Edu./SKNCOA/2023/ 151

Date: 04.02.2023

Request for Quotation

Sealed Quotation are invited from the Registered Contractors to execution of the following works in the attached 'H' schedule. The quotation will be accepted up to 10.02.2023 at 12.00 P.M. and will be opened on the same day at 12.30 P.M. by the Convenor and tender committee. Relevant registration certificate of contractor must be enclosed with 'H' schedule. The Dean & FC has all right to accept/ reject any quotation without assigning the reason. Quantity can be increase/ decrease.

Name of work:- 1. Providing & Fixing of False Ceiling at Deptt. of Ext. Edu.

Estimated Cost: Rs. 90000/-

Work completion period: Five Days.

Blonr
HEAD

Copy to:-

1. The Comptroller, SKNAU, Jobner
2. The Dean & FC, SKNCOA, Jobner
3. The Convenor & Tender Committee, SKNCOA, Jobner
4. The Incharge, READY, SKNCOA, Jobner
5. Office Incharge, CIMCA for upload on website of the University.
6. The Cashier/ Accounts, Estate Office, SKNAU, Jobner.
7. Notice Board- Office
8. M/s.....
9. M/s.....
10. M/s.....

Blonr
HEAD

Name of Work: False Ceiling Work & fixing of LED Light at Deptt. of Ext. Edu. SKNCOA, Jobner
 Based on:- False Ceiling Market Rate

"H" Schedule

S. No	Item Description	Qty	Unit	Rate (Rs)	Total Amount
1.	Providing and fixing of false ceiling with grid of M.S.tube section of size 19mm X 19mm and with a wall thickness of 1mm+/- 0.2mm.The side pipe and the intermediate pipes is fixed to the roof from the top with the help of ceiling angles/wire grid shall be covered by the up PVC profile section of size 6mm X 250mm with wall thickness of 0.80mm +/- 0.2mm,with the help of self-tapping screw of 6mm X 13mm, 6mm X 19mm.Necessary cutouts for electric connections, lighting, air conditioning etc. shall be provided at required place. The perimeter edge shall be covered by extruded PVC corner beading section of size 9mm X 28mm or 25mm X30mm with a wall thickness of 1mm+/-0.2mm fixed by applying cynoacrylic adhesive complete as per manufacturer's specification and direction of Engineer-in-charge.	550	Sqm	Per Sqm _____	
2.	Providing & Fixing of IP20, 2'x2' LED Surface/ Recessed mounting Mid power SMD type LED Lightfixture not less than 50mm housing depth made from CRCA sheet steel housing, high purity / transmissivity UV stabilized Non -yellowish diffuser for uniform light distribution. High efficiency with 4 KV internal/external surge protection BIS certified isolated driver having efficiency > 85% , with Short & Open circuit protection (Integral with light fixture). System lumen efficacy of ≥ 120 lm/Watt ,THD < 10 % , p.f. ≥ 0.95 ,CRI >80 , life time of minimum 50000 Burning Hours with , 70% of initial Lumen maintained till life ends , CCT 3000°K / 4000°K / 5700°K /6000°K/6500°K (As per ANSI Bin) , maximum power consumption should not more than the specified rating and Fixture shall be of BIS standard and trade mark certificate (T.C.). Manufactures Word Mark/ Name Engraved/ Embossing/ Screen printing on housing. OEM must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 & LM80) certificate / Report from OEM shall be submitted. All as per pre approved by Engineer incharge. All as per pre approved by Engineer in charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . Minimum lumen output 3600 lm	14	Nos.	Per Unit _____	